



DUN Sp Sport 5000

Ultra-High Performance All-Season Tires



Dry Traction	Wet Traction	Snow Traction	Ride Comfort	Quiet Ride
8	8	7	8	8
Features			Benefits	
<ul style="list-style-type: none"> ◦ Innovative, asymmetrical tread design ◦ Large, stable, interconnected tread blocks ◦ Independent inner tread blocks with open shoulder grooves ◦ Full-width, twin-cut steel belts with Jointless Band Technology™ ◦ Exclusive, high-performance, all-season tread compound ◦ Max Flange Shields ◦ Dunlop Self-Supporting Technology features a patented sidewall construction and specially-developed compounds* ◦ *Only on the SP Sport 5000 DSST, SP Sport 5000 DSST CTT and SP Sport 5000 A/S DSST CTT. 			<ul style="list-style-type: none"> ◦ Optimum balance of wet and dry performance ◦ Strong dry cornering, grip and stability ◦ Powerful water dispersion and all-season grip ◦ Confident ride uniformity and excellent footprint shape ◦ Enhanced grip, control, energy absorption and tread wear in a wide range of driving and weather conditions ◦ Helps protect rims from accidental curb damage ◦ Continued mobility up to a distance of 50 miles at a maximum speed of 55 mph in normal conditions* ◦ *Only on the SP Sport 5000 DSST, SP Sport 5000 DSST CTT and SP Sport 5000 A/S DSST CTT. 	

Tire Dimension Data & Other Technical Information

Tire Size	Product Code	Material Number	Srvcs Desc	Side wall	App Rim Width (min)	App Rim Width (max)	Meas Rim Width	Overall Width	Overall Diam.	Max Load	RPM	Tread Depth (32nds)	Weight (lbs)	Limited Wmnty Miles KM	U.T.Q.G.
P195/65R15	26503856500196625	89H	BSL	5.5	7.0	6.00	8.2	24.8	1279	840	10	19.8	000	340	A A
P195/50R16	26503895200173783	83V	BSW	5.5	7.0	6.00	7.7	23.7	1074	886	10	20.8	000	360	A A
195/60R16	26503760100204870	89H	BSW	5.5	7.0	6.00	7.9	25.2	1279	829	10	20.5	000	340	A A
P215/60R16	26501475400177717	94V	BSW	6.0	7.5	6.50	8.8	26.0	1477	840	10	23.5	000	340	A A
225/45R17	26503764700198850	91V	BSW	8.5	7.0	8.00	9.4	24.9	1356	835	10	22.9	000	340	A A
245/45R17	26503764800198881	95V	BSW	9.0	7.5	8.00	9.5	25.6	1521	813	13	25.8	000	340	A A
P245/50ZR17	26503761300173154	98W	BSW	7.0	8.5	7.50	10.0	26.7	1653	786	10	27.4	000	340	AA A
P225/55R17	26502114300207751	95H	BSW	6.0	8.0	6.50	8.8	26.8	1521	779	10	25.1	000	340	A A
P225/55R17	26503764300185228	95H	BSW	6.0	8.0	7.00	9.0	26.8	1521	784	10	24.9	000	340	A A
275/55R17	26501475600193265	109V	BSW	7.5	9.5	8.50	11.4	28.9	2271	718	11	36.0	000	360	A A
255/60R17	26501474500201202106H	BSW	7.0	9.0	8.00	10.4	29.1	2094	718	11	35.0	000	360	A A	
255/60R17	26501476000201916106H	BSW	0.0	0.0	8.50	11.1	29.1	2094	716	11	36.3	000	200	A A	
255/60R17	26503766100193406106H	VSB	7.0	9.0	7.50	10.2	29.1	2094	722	11	31.0	000	340	A A	
P215/45R18	26502514500203379	89V	BSW	7.0	8.0	7.00	8.1	25.7	1279	0	10	24.2	000	360	A A
P245/45R18	26503764500194911	96V	BSW	9.0	7.5	8.00	9.6	26.7	1565	775	10	27.6	000	340	A A
P235/50R18	26502115200207740	97V	BSW	6.5	8.5	7.50	9.5	27.1	1609	770	10	27.8	000	340	A A
P255/55R18	26503765700193408104H	VSB	7.0	9.0	8.00	10.4	29.0	1984	721	11	32.5	000	340	AA A	
265/60R18	26502526000201063110H	BSW	7.5	9.5	8.00	11.0	30.5	2337	686	0	35.9	000	200	A A	
P275/55R20	26501474100201035111H	VSB	7.5	9.5	8.50	11.2	31.9	2403	655	0	42.2	000	340	A A	